

Description

Recovery winch for military vehicles. Doubled performance allows to tow heavy military vehicles to a low-bed type trailer for maintenance, transportation and recovery purposes. Different configurations are available upon request. Fully compliant with **EN 14492**. Additional equipment and accessories are available as well.



Specifications

Maximum Pulling Capacity	: 35000 kg x2 / 66138 lbs x2
Maximum Rope Length	: 61 m / 200.1 ft
Recommended Wire Rope	: Ø26 mm / Ø1 1/32"
Hydraulic Motor	: 130 cc x2 / 7.93 in ³ x2
Maximum Pump Flow Rate	: 75 l/min x2 / 19.81 gal/min x2
Max Working Pressure	: 200 bar / 2900 psi
Weight	: 1200 kg / 2645 lbs

Additional Equipment

Standard package:

- Rope
- Roller fairlead
- Pressure roller
- Pneumatic freespool
- Hydraulic inlet G 1/2"

Optional:

- Radio control system
- ECU & IQAN equipment
- Double speed working mode
- Automatic roller fairlead
- M24 mounting bolts
- Hydraulic control valve with manual lever

Line Pull and Line Speed Performance

Winding layer	Pulling capacity (kg / lbs)	Rope speed (m/min - ft/min)	Rope length (m/ft)
1	(35000 / 77162) x2	3.37 / 11.05	11.7 / 38.5
2	(29063 / 64074) x2	4.06 / 13.31	26.0 / 85.0
3	(24849 / 54782) x2	4.74 / 15.57	42.5 / 139.3
4	(21701 / 47844) x2	5.43 / 17.82	61.4 / 201.4



Each new winch is guaranteed against defects in workmanship and material defects for a period of 24 months from date of purchase. Wire ropes are not included under warranty.